


Belt Type: 4 Ply 10/3 CFW

EP 1360/4 10 x 3 mm Cover Grade – AS-M



Belt Type: 4 Ply 10/3 – EP1360/4 10 x 3 mm Cover Grade – AS-M					
Belt Dimensions	Properties			Dimension	Acc. AS
		Width	B	750 ~2200	mm
	Thickness of belt	S1	~ 21.1	mm	AS1332
	Thickness of top cover	S2	10	mm	AS1332
	Thickness of bottom cover	S3	3	mm	AS1332
	Nominal breaking strength		≥ 1360	KN/m	AS1332
	Weight		~ 25.2	KG/m ²	AS1332
Tension Member	PLY Type	EP			
	Number of Plies	4			
Cover	Type of rubber compound	AS-M			
	Tensile strength (min.)	≥24		MPa	AS1332
	Elongation at break (min.)	≥450		%	AS1332
	Abrasion	≤120		mm ³	AS1332
	Hardness	65 ± 5	Shore A		AS1332
Carcass	Adhesion Cover to Ply	≥4.5		N/mm	AS1332
	Adhesion Ply to Ply	≥5.0		N/mm	AS1332
	Elongation at break	≥10		%	AS1332
	Reference Elongation	≤4,0		%	AS1332

NOTE: SOME SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

Office: 03 97066339 | Fax: 03 97066445 | Email: enquiries@allstateconveyors.com | Website:

www.allstateconveyors.com Postal: PO Box 396 Pakenham 3810 | 38 Nicole Way Dandenong Victoria 3175.