


## Belt Type: 3 Ply C25

### EP 450/3 3 x 1.5 mm Cover Grade – AS-N C25P450



Belt Type: 3 PLY C25 – EP450/3 3 x 1.5 mm Cover Grade – AS-N C25P450					
	Properties		Dimension		Acc. AS
Belt Dimensions	Width	<b>B</b>	500 ~750	mm	AS1332
	Thickness of belt	<b>S1</b>	~ 8.1	mm	AS1332
	Thickness of top cover	<b>S2</b>	3	mm	AS1332
	Thickness of bottom cover	<b>S3</b>	1.5	mm	AS1332
	Nominal breaking strength		≥ 450	KN/m	AS1332
Tension Member	PLY Type	<b>EP</b>			
	Number of Plies	3			
Cover	Type of rubber compound	<b>AS-N</b>			
	Tensile strength (min.)	≥17		N/mm <sup>2</sup>	AS1332
	Elongation at break (min.)	≥400		%	AS1332
	Abrasion	≤200		mm <sup>3</sup>	AS1332
	Hardness	65 ± 5		Shore A	AS1332
Cleat Dimensions	Width of cleat	<b>C.W</b>	450	mm	
	Height of cleat	<b>C.H</b>	25	mm	
	Pitch of cleat	<b>C.P</b>	250	mm	

NOTE: SOME SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

Office: 03 97066339 | Fax: 03 97066445 | Email: enquiries@allstateconveyors.com | Website:

www.allstateconveyors.com Postal: PO Box 396 Pakenham 3810 | 38 Nicole Way Dandenong Victoria 3175.